

KAWASAKI STEEL TECHNICAL REPORT

No.7 (March 1983)

MARIWEL - Seawater Corrosion Resistant Steel for Welded Structures

Takao Kurisu, Tsukasa Imazu, Noboru Nishiyama, Shigeharu Suzuki, Taketo Okumura,
Tadakazu Kyuno

Synopsis :

Three types of weldable seawater corrosion resistant steels, "MARIWEL", have been developed: MARIWEL H50 is a 50kgf/mm² class low alloy steel containing Cu, Ni and Mo, and has a good corrosion resistance in splash zone; MARIWEL K is a 41 or 50kgf/mm² class low alloy steel containing Cr and Mo, and has a good corrosion resistance in submerged zone; and MARIWEL L R is a 41 or 50kgf/mm² class low alloy steel containing Cr, Cu and Ni, which shows good corrosion resistance in both splash and submerged zone. The test results for the commercially produced steel plates indicate that these steels have good mechanical properties and weldabilities and well as excellent seawater-corrosion resistance. These steels show about twice corrosion resistance compared with that of ordinary steels such as SM50B.

(c)JFE Steel Corporation, 2003

The body can be viewed from the next page.

MARIWEL—Seawater Corrosion Resistant Steel for Welded Structures*

Shinjiro SUGIYAMA, Tetsuo OKAMURA and Tetsuo KUROKI

Three types of weldable seawater corrosion resistant steel "MARIWEL" have

| Site properties (JIS No.1A) | | | Charpy impact |
|-----------------------------|---|---------------------|----------------------------------|
| Joint | Tensile strength (kgf/mm ²) | Elongation min. (%) | value, min. $\sqrt{E_0}$ (kgf·m) |
| | 50-62 | 18 | — |
| | | 21 | 2.8 |
| | 41-52 | 19 | — |
| | | 22 | 2.8 |
| | 50-62 | 18 | — |
| | | 21 | 2.8 |
| | 41-52 | 19 | — |
| | | 22 | 2.8 |
| | 50-62 | 18 | — |
| | | 21 | 2.8 |

Table 5 Chemical composition of weld metals(%)

| Designation | Electrode | C | Si | Mn | P | S | Cu | Ni | Cr | Mo |
|--------------|-----------|-------|------|------|-------|-------|------|------|------|------|
| MARIWEL H50C | KSM-50H | 0.038 | 0.61 | 0.98 | 0.014 | 0.004 | 0.36 | 0.27 | — | 0.17 |
| MARIWEL K50C | KSM-50K | 0.040 | 0.58 | 0.88 | 0.014 | 0.005 | — | — | 1.00 | 0.19 |
| MARIWEL R50C | KSM-50R | 0.041 | 0.55 | 0.87 | 0.015 | 0.004 | 0.31 | 0.22 | 1.08 | — |

3.1 Characteristics of Base Metal

The mechanical properties of the base metal are shown in Table 4. Both strength and toughness satisfy




characteristics.

3.2 Weldability and Properties of Welded Joint

The coated electrodes shown in Table 5 have the same chemical composition as that of the base metal so as to bring the seawater corrosion resistance to






4 Seawater Corrosion Resistance

From the commercial steels of MARIWEL H50C and R50C, long ($8t \times 50 \times 5500$ mm) and short ($8t \times 200 \times 300$ mm) test-pieces were made and subjected to a seawater corrosion test for 3–4 years at Chiba, with SM50B and MARINER steel used as the reference material. The surface of the test-piece was finished by machine grinding.

The corrosion rate determined from the mean decrease of thickness in the long test-pieces is shown in Fig. 4. Evidently, the long test-piece extending from the atmospheric zone to the underground zone indicated a general tendency for the splash and submerged zones to show greater corrosion rate and for the atmospheric, tidal and underground zones to give relatively smaller corrosion rates. MARIWEL H50C, K50C and R50C gave corrosion rates about a half of that of ordinary steel at the splash zone, the submerged zone and both splash and submerged zones, respectively, proving their excellent corrosion resistance.

As shown in Photo 1, the corroded surface of MARIWEL R50C was fine-pitted in the splash zone, while pitting became increasingly irregular in the tidal

Corrosion rate per one side (mm/year)






Fig. 5 Results of seawater exposure tests at Chiba (Specimen: 8t × 200 × 300 mm)

the corrosion advanced linearly in respect of time in the splash zone for MARIWEL H50C and in the

environments was about twice as good as that of the ordinary steel